



**examkill**  
affordable exams preparation material

# Cisco

500-901

*Cisco Data Center Unified Computing Infrastructure Design*

- **Up to Date products, reliable and verified.**
- **Questions and Answers in PDF Format.**

**For More Information – Visit link below:**

**<https://www.examkill.com/>**

## Version product

---

## Question: 1

What is the purpose of a virtual switch?

- A. Virtual switches manage storage requests from virtual machines
- B. Virtual switches present NiCs to virtual machines for network connectivity
- C. Virtual switches recommend QoS options to the hypervisor for network connectivity
- D. Virtual switches present NICs to the UCSM for network connectivity

**Answer: B**

## Question: 2

You dissociated a Database Server Service Profile from your existing UCS C240 M4. Then, you associate a Web Server Service Profile to this UCS C240 M4. The Database Server Service Profile enabled a Scrub Policy enabled for Disk Scrub. The Web Server Service Profile contains a Scrub Policy disabled 'or Disk Scrub. What will happen after the reboot?

- A. The process will fail because the Service Profiles are fundamentally efferent
- B. The process will succeed, and server disk content will be preserved
- C. The process will fail because of the differences in the Scrub Policies
- D. The process will succeed, but server disk content will be lost

**Answer: C**

## Question: 3

You are creating Boot Policy to have your Cisco UCS Server boot from SAN. What option shows the correct process?

- A. Include a vHBA in the Boot Order list, provide a Boot LUN ID, and provide the WWPN address for the Boot Target.
- B. Include a vHBA in the Boot Order list, provide a SAN ID, and provide the WWPN address for the Boot Target.
- C. Include two VHBAs in the Boot Order list (vHBA-A and vHBA-B for redundancy0, provide a Boot Lun ID for each vHBA, and provide the WWPN address for the Boot Target.
- D. Include two vHBAs in the Boot Order list (vHBA-A and vHBA-B for redundancy), provide a SAN ID, and provide the WWPN address for the Boot Target.

**Answer: A**

---

## Question: 4

An administrator has configured an NPV traffic map for a new server interface, none of the uplinks in the traffic map are operational. What is the resulting action?

- A. The traffic map will be disregarded and an uplink in the interface VSAN will be selected
- B. The default VSAN uplink will be used if operational.
- C. The server will remain in a nonoperational state.
- D. The server interface will signal an FDISC message to the fabric switch.

**Answer: C**

---

For More Information – **Visit link below:**

**<https://www.examkill.com/>**

## FEATURES:

- 100% Pass Guarantee
- 30 Days Money Back Guarantee
- 24/7 Live Chat Support(Technical & Sales)
- Instant download after purchase
- 50,000 +ve Reviews
- 100% Success Rate
- Discounts Available for Bulk Orders
- Updates are free for 90 days
- Verified answers by experts

