

Click the link below to get **more detail**
<http://www.examkill.com/>

ExamCode: NCS_20022252020
ExamName: NCSS 2G/3G SCN PaO 2.2
Vendor Name: Nokia
Edition = DEMO

Version: 7.0

Question: 1

Introduction of HD Voice into a network will impact which of the following MGW functional units?

- A. ISU/CLA, IPNIP/NGEP, TCUs
- B. IPNIP/NPGEP and TCUs
- C. TCUs
- D. No impact on MGW HW

Answer: B

Question: 2

Why do we need NW Assessment?

- A. It is required to collect the existing network information and status for Network Design & Optimization.
- B. To commission NEs.
- C. For KPI monitoring.
- D. For databuild creation.

Answer: A

Question: 3

Benefit(s) of introducing load balancing to MSS:

- A. Decrease number of IP links
- B. Decrease number of VMGWs
- C. Hide internal MSS topology
- D. All of the above.

Answer: D

Question: 4

CSFB Solution is required for?

- A. To facilitate the early introduction of LTE in the network, before the introduction of IMS_VoLTE.
- B. CSFB is required when coverage of VoLTE is not widely deployed, it allows subscriber to Fall Back to CS during the call when moves outside VoLTE coverage.
- C. CSFB is a new type of Handover introduced to the network that works in connected mode. It allows the MSS to share the MGW resources with MME to offer required services to LTE handsets.
- D. All of the above.

Answer: A

Question: 5

The reasons for operator to migrate to ATCA MGW from the IPA MGW are:

- A. ATCA MGW have lower foot print, higher capacity and better power efficiency in comparison to IPA MGW.
- B. ATCA MGW supports all interface types ATM/TDM/IP unlike the IPA.
- C. IPA reached end of support and all customers must upgrade now to ATCA.
- D. ATCA MGW is required for new features like SRVCC, HD voice, RTP multiplexing.

Answer: A

Question: 6

Who is responsible for Network Element's services cost?

- A. Care Engineer
- B. Project Manager
- C. Service Product Manager
- D. NPO Engineer

Answer: C

Question: 7

Which CS Core Optimization below is part of the available services?

- A. CS Core capacity optimization
- B. Feature Introduction
- C. CS Core optimization
- D. All of the above.

Answer: D

Question: 8

Which document(s) need to get customer approval before proceeding with databuild?

- A. HLD and RFP.
- B. HLD and LLD.
- C. No approval required.
- D. Dimensioning document.

Answer: B

Question: 9

The protocol used for CSFB between MME & VLR is:

- A. SGSAP
- B. SIP
- C. MAP
- D. GTP

Answer: A

Click the link below to get [more details](http://www.examkill.com/)
<http://www.examkill.com/>

FEATURES:

- 100% Pass Guarantee
- 30 Days Money Back Guarantee
- 24/7 Live Chat Support (Technical & Sales)
- Instant Download or Email Attachment
- 50,000 +ve Reviews
- 100% Success Rate
- Discounts Available for Bulk Orders



We Accept

